



OFM432XT

10GBase-LR Single-Mode SFP+ transceiver (up to 10 km)



OFM432XT is an unidirectional SFP+ transceiver with 10GBase-LR port for single-mode optical cable (up to 10 km).

The OFM432XT is equipped with a standard duplex LC connector and is designed to work with 9/125 um single-mode fiber. The transceiver provides data transmission at speeds up to 10 Gbps at a distance of up to 10 km. Operating wavelength is 1310 nm.

The OFM432XT complies with SFP+ MSA specifications and is hot-pluggable.

Key Features

- Enhanced Small Form-factor Pluggable (SFP+)
- 1x10GBase-LR port
- Duplex LC connector
- Fiber type: 9/125 um single-mode
- Maximum fiber cable length up to 10 km
- Operating wavelength 1310 nm
- Hot-pluggable



Specifications

Hardware

Transceiver Type	<ul style="list-style-type: none">• SFP+
Interfaces	<ul style="list-style-type: none">• 1x10GBase-LR port
Connector	<ul style="list-style-type: none">• Duplex LC
Uni-/Bi-directional	<ul style="list-style-type: none">• Uni-directional
Data Rate	<ul style="list-style-type: none">• 10 Gbps
Maximum Fiber Cable Length	<ul style="list-style-type: none">• 10 km
Fiber Type	<ul style="list-style-type: none">• 9/125 um Single-mode Fiber
Wavelength	<ul style="list-style-type: none">• 1310 nm
Transmit Power Range	<ul style="list-style-type: none">• 0 to -6 dBm
Receive Power Range	<ul style="list-style-type: none">• 0.5 to -14.4 dBm
Sensitivity	<ul style="list-style-type: none">• -14.4 dBm
Standard	<ul style="list-style-type: none">• IEEE 802.3ae 10GBase-LR
Supported Features	<ul style="list-style-type: none">• Hot swap• MSA compliant• RoHS compliant

Physical Parameters

Dimensions (L x W x H)	<ul style="list-style-type: none">• 47.5 x 13.7 x 8.5 mm
------------------------	--

Operating Conditions

Power Support	<ul style="list-style-type: none">• 3.3 V
Supply Current	<ul style="list-style-type: none">• 300 mA
Temperature	<ul style="list-style-type: none">• Operating: 0 to 70 °C• Storage: -40 to 85 °C
Humidity	<ul style="list-style-type: none">• Operating: 0% to 85%• Storage: 0% to 85%

Package Contents

Package Contents	<ul style="list-style-type: none">• OFM432XT Transceiver
------------------	--



Order Info

OFM432XT

SFP+ Transceiver, 10GBase-LR (Duplex LC), 1310nm,
Single-mode fiber, up to 10km
