



OFM712

1000Base-T SFP Transceiver (up to 100 m)



OFM712 is an SFP transceiver with 1x1000Base-T port for twisted-pair network cable (up to 100 m).

The OFM712 is equipped with RJ-45 connector and is designed to work on the common Category 5 twisted-pair network cable. The transceiver provides data transmission at speeds up to 1.25 Gbps at a distance of up to 100 m.

The OFM712 complies with SFP MSA specifications and is hot-pluggable.

Key Features

- Small Form-Factor Pluggable (SFP)
- 1x1000Base-T port
- RJ-45 connector
- Cable type: Category 5 twisted-pair cable
- Maximum fiber cable length up to 100 m
- Hot-pluggable



Specifications

Hardware

Transceiver Type	<ul style="list-style-type: none">• SFP
Interfaces	<ul style="list-style-type: none">• 1x1000Base-T port
Connector	<ul style="list-style-type: none">• RJ-45
Data Rate	<ul style="list-style-type: none">• 1.25 Gbps
Maximum Fiber Cable Length	<ul style="list-style-type: none">• 100 m
Cable Type	<ul style="list-style-type: none">• Category 5 twisted-pair cable
Standard	<ul style="list-style-type: none">• IEEE 802.3-2002• IEEE 802.3ab 1000Base-T
Supported Features	<ul style="list-style-type: none">• Auto-MDI/MDIX adjustment• Hot swap• MSA compliant• RoHS compliant

Physical Parameters

Dimensions (L x W x H)	<ul style="list-style-type: none">• 45 x 13.4 x 8.5 mm
------------------------	--

Operating Conditions

Power Support	<ul style="list-style-type: none">• 3.3 V
Supply Current	<ul style="list-style-type: none">• 375 mA
Temperature	<ul style="list-style-type: none">• Operating: 0 to 70 °C• Storage: -40 to 85 °C
Humidity	<ul style="list-style-type: none">• Storage: 5% to 95%

Package Contents

Package Contents	<ul style="list-style-type: none">• OFM712 Transceiver
------------------	--

Order Info

OFM712	SFP Transceiver, 1000Base-T (RJ45), up to 100m
--------	--