



# OU3340NPD

## 6-in-1 USB-C Docking Station

2xUSB 3.0, 1xUSB Type-C, 1xUSB Type-C/PD 3.0, 1xHDMI, 1xGigabit LAN (RJ-45)



OU3340NPD is a portable 6-in-1 docking station for devices with USB Type-C port.

The ORIGO OU3340NPD docking station has a wide range of ports for connecting additional devices to PCs and laptops equipped with USB Type-C port.

Two USB 3.0 ports allow you to connect required computer peripherals, while Gigabit Ethernet port ensures reliable connection to a wired network with Internet access at the speed of up to 1000 Mbps.

The HDMI<sup>1</sup> port with 1080p@60Hz, 4K@30Hz support allows you to connect your laptop to monitor, TV screen or projector and organize a video content streaming on a big screen in Ultra HD quality.

One of two USB-C ports supports PD 3.0 (100 W) Fast Charge technology<sup>2</sup> and allows you to charge your laptop without disconnecting the docking station.

The docking station is compatible with most operating systems, including macOS, Windows, Linux.

<sup>1</sup> DP Alt Mode support is required for HDMI proper operation.

<sup>2</sup> Please make sure that the USB Type-C port of your laptop supports PD 3.0.

### Key Features

- For PCs and laptops with USB Type-C port
- 2 USB 3.0 ports for computer peripherals
- HDMI port with 1080p@60Hz, 4K@30Hz support
- Gigabit Ethernet port with network activity LED
- USB-C port for transmitting data
- USB-C/PD 3.0 (100 W) port for fast charging your laptop
- macOS, Windows, Linux support



## Specifications

### Hardware

Connector for Connecting PC	<ul style="list-style-type: none"><li>• USB Type-C</li></ul>
Ports	<ul style="list-style-type: none"><li>• 2 USB 3.0 Type-A ports (up to 5 Gbps)</li><li>• 1 HDMI port (1080p @ 60 Hz, 4K @ 30 Hz)</li><li>• 1 Gigabit Ethernet (RJ-45) port (up to 1000 Mbps)</li><li>• 1 USB Type-C port</li><li>• 1 USB Type-C/PD 3.0 port (100 W)</li></ul>
Standards	<ul style="list-style-type: none"><li>• USB 3.0</li><li>• USB 2.0</li><li>• USB 1.1</li><li>• IEEE 802.3 10Base-T</li><li>• IEEE 802.3u 100Base-TX</li><li>• IEEE 802.3ab 1000Base-T</li></ul>
Casing	<ul style="list-style-type: none"><li>• Aluminium</li></ul>

### System Requirements

PC Minimum Requirements	<ul style="list-style-type: none"><li>• Available USB Type-C port with DP Alt Mode support</li><li>• Compatible OS:<ul style="list-style-type: none"><li>- Windows 7/8/8.1/10/11</li><li>- Linux 2.6 and higher</li><li>- Mac OS 10.x and higher</li></ul></li></ul>
-------------------------	--

### Physical Parameters

Dimensions (W × D × H)	<ul style="list-style-type: none"><li>• 125 x 32 x 10 mm</li></ul>
Weight	<ul style="list-style-type: none"><li>• 51 g</li></ul>
Package Dimensions	<ul style="list-style-type: none"><li>• 14.5 x 7.8 x 1.8 cm</li></ul>

### Operating Conditions

Power Input	<ul style="list-style-type: none"><li>• From computer (from USB bus)</li></ul>
PD Power	<ul style="list-style-type: none"><li>• 100 W</li></ul>
Temperature	<ul style="list-style-type: none"><li>• Operating: 0 to 45 °C</li><li>• Storage: -10 to 70 °C</li></ul>
Humidity	<ul style="list-style-type: none"><li>• Operating: up to 85% (non-condensing)</li><li>• Storage: up to 85% (non-condensing)</li></ul>



---

**Package Contents**

Package Contents	<ul style="list-style-type: none"><li>• OU3340NPD Docking Station</li><li>• Quick Installation Guide</li></ul>
------------------	--

**Order Info**

OU3340NPD	USB-C Docking Station, 2xUSB 3.0, 1xUSB-C/PD 3.0, 1xUSB-C, 1x1000Base-T, 1xHDMI
-----------	---