



OU3350SNPD

9-in-1 USB-C Docking Station

1xUSB 3.0, 2xUSB 2.0, 1xHDMI, 1xGigabit LAN (RJ-45), 1xUSB Type-C/PD 3.0, 1xSD/TF/microSD, 1x3.5mm mini jack (TRRS), 1x3.5mm mini jack (Mic)



OU3350SNPD is a portable 9-in-1 docking station for devices with USB Type-C port.

The ORIGO OU3350SNPD docking station has a wide range of ports for connecting additional devices to PCs and laptops equipped with USB Type-C port.

Two USB 2.0 ports and one USB 3.0 port allow you to connect required computer peripherals, while Gigabit Ethernet port ensures reliable connection to a wired network with Internet access at the speed of up to 1000 Mbps.

The HDMI¹ port with 4K@60Hz support allows you to connect your laptop to monitor, TV screen or projector and organize a video content streaming on a big screen in Ultra HD quality.

The USB-C port supports PD 3.0 (100 W) Fast Charge technology² and allows you to charge your laptop without disconnecting the docking station.

The OU3350SNPD docking station has also SD/TF/microSD card slots and 3.5 mm audio connectors³ for connecting headset and microphone.

The docking station is compatible with Windows 10/11 and macOS 14 operating systems.

¹ DP Alt Mode support is required for HDMI proper operation.

² Please make sure that the USB Type-C port of your laptop supports PD 3.0.

³ TRRS and Mic audio connectors can not be used simultaneously.



Key Features

- For PCs and laptops with USB Type-C port
- Two USB 2.0 ports and one USB 3.0 port for computer peripherals
- HDMI port with 4K@60Hz support
- Gigabit Ethernet port
- SD/TF/microSD card reader
- 3.5 mm audio connector for headset/headphones
- 3.5 mm audio connector for microphone
- USB-C/PD 3.0 (100 W) port for fast charging
- Windows OS 10/11 and macOS 14 support



Specifications

Hardware

| | |
|-----------------------------|--|
| Connector for Connecting PC | <ul style="list-style-type: none">• USB Type-C |
| Ports | <ul style="list-style-type: none">• 1 USB 3.0 Type-A port (up to 5 Gbps)• 2 USB 2.0 Type-A ports (up to 480 Mbps)• 1 HDMI port (4K @ 60 Hz)• 1 Gigabit Ethernet (RJ-45) port (up to 1000 Mbps)• 1 USB Type-C/PD 3.0 port (100 W)• SD/TF/microSD card slots• 3.5 mm audio connector (Mic)• 3.5 mm audio connector, 4 pins (TRRS) |
| Standards and Functions | <ul style="list-style-type: none">• USB version 3.0 specification• USB version 2.0 specification• USB version 1.1 specification• IEEE 802.3 10Base-T• IEEE 802.3u 100Base-TX• IEEE 802.3ab 1000Base-T |
| Casing | <ul style="list-style-type: none">• Anodized aluminium |

System Requirements

| | |
|-------------------------|--|
| PC Minimum Requirements | <ul style="list-style-type: none">• Available USB Type-C port with DP Alt Mode support• Compatible OS:<ul style="list-style-type: none">- Windows OS 10/11- macOS 14 |
|-------------------------|--|

Physical Parameters

| | |
|------------------------|---|
| Dimensions (W × D × H) | <ul style="list-style-type: none">• 180 x 35 x 12 mm |
| Weight | <ul style="list-style-type: none">• 90 g |
| Package Dimensions | <ul style="list-style-type: none">• 22.5 x 9.2 x 3.2 cm |
| Gross Weight | <ul style="list-style-type: none">• 0.15 kg |

Operating Conditions

| | |
|-------------|--|
| Power Input | <ul style="list-style-type: none">• From computer (from USB bus) |
| PD Power | <ul style="list-style-type: none">• 15-100 W |



| | |
|-------------|---|
| PD Voltage | <ul style="list-style-type: none">• 5-20 V |
| Temperature | <ul style="list-style-type: none">• Operating: 0 to 50 °C• Storage: -10 to 68 °C |
| Humidity | <ul style="list-style-type: none">• Operating: 5% to 85% (non-condensing)• Storage: 5% to 85% (non-condensing) |

Package Contents

| | |
|------------------|---|
| Package Contents | <ul style="list-style-type: none">• OU3350SNPD Docking Station• Quick Installation Guide |
|------------------|---|

Order Info

| | |
|------------|---|
| OU3350SNPD | USB-C Docking Station, 1xUSB 3.0, 1xUSB-C/PD 3.0, 2xUSB 2.0, 1x1000Base-T, 1xHDMI, SD/TF/microSD slot |
|------------|---|