



OF3208

6-Port Gigabit Ethernet Network Platform with 2xGigabit SFP Ports

6x1000Base-T, 2x1000Base-X SFP, 2xUSB, 1xConsole RJ-45, rack mounting



The OF3208 is a network platform with 6x1000Base-T ports, 2x1000Base-X SFP ports, 2xUSB ports and console RJ-45 port.

The ORIGO OF3208 is a cost-effective, high performance 1U rackmount network platform based on Intel Celeron 3865U dual-core CPU. The Celeron 3865U CPU is targeted at UTM, firewall, VPN, IPS and WAN optimization applications from SMB to Enterprise environment.

Key Features

- 6x1000Base-T ports
- 2x1000Base-X SFP ports
- 2xUSB ports
- 1xConsole RJ-45 port
- 1xVGA port
- CPU: Intel Celeron 3865U (1.8 GHz, dual-core)
- RAM: 8 GB, DDR3
- Rack mounting



Product Specifications

Hardware Specifications

CPU and Memory	<ul style="list-style-type: none">• CPU: Intel Celeron 3865U (1.8 GHz, dual-core)• RAM: 8 GB, DDR3• Storage: 64 GB, mSATA
Interfaces	<ul style="list-style-type: none">• 6 10/100/1000Base-T (RJ-45) ports• 2 1000Base-X SFP ports• 1 Console RJ-45 port• 2 USB 2.0 ports• 1 VGA port
LEDs	<ul style="list-style-type: none">• Power• Storage
Buttons	<ul style="list-style-type: none">• Reset
Power	<ul style="list-style-type: none">• Power input (AC)
Ventilation	<ul style="list-style-type: none">• 2 fans
Mounting	<ul style="list-style-type: none">• 19" rack mountable

Physical Parameters

Dimensions (L x W x H)	<ul style="list-style-type: none">• 432 x 266 x 46 mm
Weight	<ul style="list-style-type: none">• 4.2 kg

Operating Conditions

Power	<ul style="list-style-type: none">• 100-240VAC, 50/60 Hz
Temperature	<ul style="list-style-type: none">• Operating: 0 to 45 °C• Storage: -20 to 70 °C
Humidity	<ul style="list-style-type: none">• Operating: 0% to 95% non-condensing• Storage: 0% to 95% non-condensing

Delivery

Package Contents	<ul style="list-style-type: none">• OF3208 Network Platform• Power cord• Rack mounting kit
------------------	--

Ordering Information



OF3208/A1A	Network Platform, 6x1000Base-T, 2x1000Base-X SFP, 2xUSB, RJ45 Console
------------	--
