



OWR1530AXG

AX1500 Wi-Fi 6 Mesh Gigabit Router

Wi-Fi 6 (802.11ax), 2.4/5GHz, 1x1000Base-T WAN, 3x1000Base-T LAN, wall mounting



OWR1530AXG is a dual-band AX1500 Wi-Fi 6 Mesh gigabit router with 1 1000Mbps WAN port and 3 1000Mbps LAN ports.

The ORIGO OWR1530AXG wireless router is designed to set up home networks with uninterrupted internet access with plans of up to 1000Mbps, high-speed dual-band Wi-Fi 6, support for IPTV in Ultra HD quality and parental control functions.

Wi-Fi operates in two frequency bands: with speeds of up to 1201Mbps in the 5GHz band and up to 300Mbps in the 2.4GHz band. Support for Mesh Wi-Fi allows to connect several OWR1530AXG routers into one network and provide seamless Wi-Fi coverage in country houses, multi-room apartments, and other premises with large area and complicated layout.

The router is fully adapted to work with IPTV, supports the creation of a guest Wi-Fi network with WPA3 protection and parental control functionality with using a URL filter and the SkyDNS content filtering service.



Key Features

- For internet plans with speeds up to 1000Mbps
- AX1500 Wi-Fi 6 with speeds of up to 1201Mbps in the 5GHz band and up to 300Mbps in the 2.4GHz band
- 1 Gigabit WAN port, 3 Gigabit LAN ports
- 4 omnidirectional 5dBi antennas
- Mesh Wi-Fi support to extend wireless coverage
- MU-MIMO and OFDMA for simultaneous operation without lags or interruptions
- Smooth IPTV streaming in HD and Ultra HD quality
- Parental control functions
- Wall mounting available

Specification

Hardware

Processor	<ul style="list-style-type: none">• RTL8197H (1GHz)
RAM	<ul style="list-style-type: none">• 128MB, DDR2
Flash	<ul style="list-style-type: none">• 128MB, SPI NAND
Ports	<ul style="list-style-type: none">• 1 10/100/1000BASE-T WAN port• 3 10/100/1000BASE-T LAN ports
LEDs	<ul style="list-style-type: none">• Power• WAN• LAN1• LAN2• LAN3• 2.4 GHz• 5 GHz• WPS• FW Update
Buttons	<ul style="list-style-type: none">• ON/OFF button to power on/power off• RESET button to restore factory default settings• Wi-Fi button to enable/disable wireless network• WPS button to connect mesh network devices and set up wireless connection



Antennas	<ul style="list-style-type: none">• 4 external non-detachable omnidirectional 5dBi antennas
MIMO	<ul style="list-style-type: none">• 2 x 2, MU-MIMO
Power Connector	<ul style="list-style-type: none">• Power input connector (DC)
Mounting	<ul style="list-style-type: none">• Desktop• Wall

Wi-Fi Parameters

Standards	<ul style="list-style-type: none">• IEEE 802.11ax• IEEE 802.11ac Wave 2• IEEE 802.11a/b/g/n• IEEE 802.11k/v• IEEE 802.11w
Frequency Range	<ul style="list-style-type: none">• 2400 ~ 2483.5MHz• 5150 ~ 5350MHz• 5650 ~ 5850MHz
Wireless Connection Rate	<ul style="list-style-type: none">• 2.4GHz<ul style="list-style-type: none">- 11n: up to 300Mbps- 11g: up to 54Mbps- 11b: up to 11Mbps• 5GHz<ul style="list-style-type: none">- 11ax: up to 1201Mbps- 11ac: up to 867Mbps- 11n: up to 300Mbps- 11a: up to 54Mbps
Wireless Connection Security	<ul style="list-style-type: none">• WPA/WPA2 (Personal/Enterprise)• WPA3 (Personal)• MAC filter• WPS (PBC/PIN)
Advanced Functions	<ul style="list-style-type: none">• Support of Mesh Wi-Fi• WMM (Wi-Fi QoS)• Information on connected Wi-Fi clients• Advanced settings• Guest Wi-Fi / support of MBSSID

	<ul style="list-style-type: none">• Rate limitation for wireless network• Periodic scan of channels, automatic switch to least loaded channel• Support of 5GHz TX Beamforming• Autonegotiation of channel bandwidth in accordance with environment conditions (20/40 Coexistence)• Support of OFDMA technology• Support of TWT technology• Support of Band Steering
Transmitter Output Power	<ul style="list-style-type: none">• Less than 20dBm (100mW)
Receiver Sensitivity	<ul style="list-style-type: none">• 2.4GHz<ul style="list-style-type: none">- 11b (11Mbps): -79dBm- 11g (54Mbps): -68dBm- 11n (HT20): -67dBm- 11n (HT40): -64dBm• 5GHz<ul style="list-style-type: none">- 11a: -74dBm- 11n (HT20): -70dBm- 11n (HT40): -67dBm- 11ac (VHT20): -67dBm- 11ac (VHT40): -61dBm- 11ac (VHT80): -57dBm- 11ax (HE20): -64dBm- 11ax (HE40): -61dBm- 11ax (HE80): -58dBm

Software

Operating Modes	<ul style="list-style-type: none">• Router• Access point• Wi-Fi client• Wi-Fi repeater• WISP repeater
WAN Connection Types	<ul style="list-style-type: none">• PPPoE• IPv6 PPPoE• PPPoE Dual Stack• Static IPv4 / Dynamic IPv4• Static IPv6 / Dynamic IPv6• PPPoE + Static IP (PPPoE Dual Access)• PPPoE + Dynamic IP (PPPoE Dual Access)• PPTP/L2TP + Static IP• PPTP/L2TP + Dynamic IP
Network Functions	<ul style="list-style-type: none">• DHCP server/relay• Advanced configuration of built-in DHCP server• Stateful/Stateless mode for IPv6 address assignment, IPv6 prefix delegation• Automatic obtainment of LAN IP address (for access point/repeater/client modes)• DNS relay• Dynamic DNS• Static IPv4/IPv6 routing• IGMP/MLD Proxy• RIP• Support of UPnP• Support of VLAN• WAN ping respond• Support of SIP ALG• Support of RTSP• WAN failover• Autonegotiation of speed, duplex mode, and flow control / Manual speed and duplex mode setup for each Ethernet port

	<ul style="list-style-type: none">• Built-in UDPXY application• Wake-on-LAN support
Firewall	<ul style="list-style-type: none">• Network Address Translation (NAT)• Stateful Packet Inspection (SPI)• IPv4/IPv6 filter• MAC filter• URL filter• Ad blocking function• DMZ• Virtual servers• Built-in SkyDNS web content filtering service
VPN	<ul style="list-style-type: none">• IPsec/PPTP/L2TP/PPPoE pass-through• PPTP/L2TP tunnels• L2TP over IPsec client• IPsec tunnels<ul style="list-style-type: none">- Transport/Tunnel mode- IKEv1/IKEv2 support- DES encryption- NAT Traversal- Support of DPD (Keep-alive for VPN tunnels)
Management and Monitoring	<ul style="list-style-type: none">• Local and remote access to settings through SSH/TELNET/WEB (HTTP/HTTPS)• Web-based interface for configuration and management• Notification on connection problems and auto redirect to settings• Firmware update via web-based interface• Automatic notification on new firmware version• Saving/restoring configuration to/from file• Support of logging to remote host• Automatic synchronization of system time with NTP server and manual time/date setup• Ping utility• Traceroute utility• TR-069 client• Schedules for rules and settings of firewall, automatic reboot, and enabling/disabling wireless network and Wi-Fi filter



- Automatic upload of configuration file from server of internet service provider (Auto Provision)
- Configuration of action for hardware buttons

Physical Parameters

Device Dimensions (L x W x H)	<ul style="list-style-type: none">• 190 x 119 x 40 mm
Device Weight	<ul style="list-style-type: none">• 260 g
Package Dimensions	<ul style="list-style-type: none">• 25.5 x 22.8 x 5.6 cm

Operating Conditions

Power	<ul style="list-style-type: none">• Output: 12V DC, 1A
Max Power Consumption	<ul style="list-style-type: none">• 9W
Temperature	<ul style="list-style-type: none">• Operating: from 0 to 40 °C• Storage: from -10 to 70 °C
Humidity	<ul style="list-style-type: none">• Operating: from 10% to 90%• Storage: from 5% to 95%

Package Contents

Package Contents	<ul style="list-style-type: none">• Router OWR1530AXG• Power adapter• Ethernet cable• Quick Installation Guide
------------------	---

Order Info

OWR1530AXG	AX1500 Wi-Fi 6 Router, 1000Base-T WAN, 3x1000Base-T LAN
------------	---